



FLEET SAE 25W60

DESCRIPTION:

Fleet SAE 25W60 Motor Oil provides high quality engine protection under all driving conditions and is specifically formulated to provide extra protection against the harmful effects of city driving. **Fleet SAE 25W60 Motor Oil** low friction formula helps improve gas mileage, extend engine life and helps protect against rust, corrosion, startup wear and varnish build-up. It also protects against thermal breakdown which helps prevent stuck rings. **Fleet SAE 25W60 Motor Oil** has a dielectric strength above 35kV and is non-conductive.

FEATURES/BENEFITS:

- Protects engines under all driving conditions
- Lowers friction and improves gas mileage
- Provides longer engine life
- Protects against rust, corrosion and varnish
- Resists thermal break-down

APPLICATIONS:

- On the highway applications for light and heavy duty trucking.
- Off the highway applications such as trucking, construction, agriculture and quarrying.
- Various mixed fleet applications.

Meets Performance Requirements:

- API CH-4, CF-4, CD
- API SL, SJ, SH, SG

* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

TYPICAL TEST DATA

SAE GRADE	25W60
Specific Gravity @ 60 °F	0.8909
Viscosity, Kinematic	
cSt at 40°C	232.7
cSt at 100°C	23.7
Viscosity Index	127
Cold Crank, cP at °C, Max	13,000 @ -10C
Flash Point, °F	398
Pour Point, °C (°F)	-23 (-9)
Color	GREEN
TBN	8.0

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.