



TERPEL SAE 25W-60 API CH-4/SL

DESCRIPTION:

Terpel SAE 25W-60 API CH-4 / SL provides high quality engine protection under all driving conditions and is specifically formulated to provide extra protection against the harmful effects of city driving.

This engine oil has a low friction formula helps improve gas mileage, extend engine life, and helps protect against rust, corrosion, startup wear and varnish build-up. It also protects against thermal breakdown which helps prevent stuck rings.

BENEFITS:

- Protects engines under all driving conditions.
- Lowers friction and improves gas mileage.
- Provides longer engine life.
- Protects against rust, corrosion and varnish.
- Resiste la descomposición térmica.
- Resists thermal break-down.

APLICATIONS:

Terpel SAE 25W-50 has a good performance on the highway applications for light and heavy-duty trucking and in off the highway applications such as trucking, construction, agriculture, and quarrying. Also, it can be used in various mixed fleet applications.

Meets the requirements and specifications of:

- API CH-4, CF-4, CD
- API SL, SJ, SH, SG

ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

TYPICAL TEST DATA:

PROPERTIES	RESULTS
Specific Gravity, (60°F)	0.8909
Viscosity, @ 40°C, cSt	168.9
Viscosity, @ 100°C, cSt	23.0
Viscosity Index	164
CCT, cP at °C, Max	13,000 @ -10C
Flash Point, °F	400
Pour Point, °C(°F)	-23 (-9)
Color,	GREEN
TBN	7.0

* Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.